

Clifton Ultrasonic Baths SW Series Ultrasonic Baths

Clifton Range[®]



These industrial strength ultrasonic baths are designed for demanding applications. The baths are also ideal for cleaning delicate or fragile components which may otherwise be damaged by mechanical cleaning.

Supplied complete with lid and basket.

The baths are available from 1 to 30 litres capacity and feature eco and dynamic sonic modes. Eco offers quieter gentler ultrasonic activity whilst dynamic running provides vigorous cleaning.

The touch pad, wipe clean, control panel with rotary dials for time and temperature, can be set between 30°C and 80°C in 5°C increments. The timer can be selected to operate between 1-30 minutes or continuously up to 6 hours.

Clifton ultrasonic baths are constructed from high quality stainless steel for durability, with side lifting handles on models SW3H upwards for easy transportation.



Clifton Ultrasonic Baths

SW Series Ultrasonic Baths

	SW1H	SW3H	SW6H
GENERAL			
Temp. Range	30°C - 80°C in 5°C increments		
Temp. Control	Analogue dial pointer		
Timer	Time setting OFF, 1, 2, 3, 4, 5, 10, 15, 20, 25, 30 minutes or continuous		
Voltage	120V or 230V models 50-60Hz		
Ultrasonic Effective Power	30W	80W	150W
Ultrasonic Peak Power/ Frequency	240W / 37kHz	320W / 37kHz	600W / 37kHz
Heater Power (220-240V)	60W	200W	400W
Drain Tap Fitted	<input type="checkbox"/>		<input checked="" type="checkbox"/>
Complete with Lid & Basket	<input checked="" type="checkbox"/>		
DIMENSIONS			
Nominal Tank Capacity	1 Litre	3 Litre	6 Litre
External (mm)	235w x 135d x 190h	305w x 190d x 230h	370w x 200d x 275h
Internal (mm)	190w x 85d x 60h	220w x 120d x 100h	275w x 125d x 150h

	SW12H	SW30H
GENERAL		
Temp. Range	30°C - 80°C in 5°C increments	
Temp. Control	Analogue dial pointer	
Timer	Time setting OFF, 1, 2, 3, 4, 5, 10, 15, 20, 25, 30 minutes or continuous	
Voltage	120V or 230V models 50-60Hz	
Ultrasonic Effective Power	200W	300W
Ultrasonic Peak Power/ Frequency	800W / 37kHz	1200W / 37kHz
Heater Power (220-240V)	800W	1200W
Drain Tap Fitted	<input checked="" type="checkbox"/>	
Complete with Lid & Basket	<input checked="" type="checkbox"/>	
DIMENSIONS		
Nominal Tank Capacity	12 Litre	30 Litre
External (mm)	380w x 290d x 330h	575w x 355d x 330h
Internal (mm)	300w x 215d x 200h	475w x 270d x 200h

Accessories



Neutral foam-inhibited cleaning concentrate

Bath	SW1H	SW3H	SW6H	SW12H	SW30H
Accessory Code	SW-CL2				