



EN 14470-1 MULTIRISK CABINETS – 105 MINUTES

CONFORMITY

- Tested and approved according to EN 14470-1 (04/2004) and EN 1363-1 (06/2000).
- Normalized labelling according to ISO 3864 and EN 14470-1 (04/2004) norms, and 92/58/CEE european directive.

- Drawer / sliding retention tray
- PVC surprotections
- Ventilation or filter casings
- Absorbent mats to be placed at the bottom of the holding tank (packets of 10 sheets)
- Possibility of yellow doors on models 794 and 795

ADVANTAGES


- Fire resistance during 105 minutes (approved Type 90) in accordance with ISO 834 fire heating curve.
- Tested and approved by an independent European laboratory.
- Possibility to separate the dangerous products families.
- Handle on the entire height of the cabinet for better ergonomics and ease of opening
- Frame allowing easy movement by pallet truck: avoids heavy handling and allows easy movement of the cabinet in case of new development
- Attractive and easy-to-use skirting board without the need for a fixing tool

TECHNICAL DATA

Please check the technical data of flammable compartment Range 11.B. (previous page).
You can also check the technical data of multirisk cabinet 7.90M in Flammable cabinets section.

OPTIONS

- Extra shelf
- Grating for retention tank



P/N	Description	Compartment type and storage capacity (L) ⁽¹⁾				Dimensions H x W x D (mm)	Delivered with			Maximum load by shelf ⁽²⁾	W. (kg)
							Containment shelves	Containment sump	Perforated cover plate		
792+M11	Under-bench cabinet 2 doors with 2 compartments	28	28	-	-	630 x 635 x 570 ⁽¹⁾	2	2	option	30	221
793+M11	Working cover cabinet 2 doors with 2 compartments	55	55	-	-	1080 x 1135 x 620 ⁽²⁾	2	2	2	30	311
793+M12	Working cover cabinet 2 doors with 3 compartments	55	28	-	28	1100 x 1137 x 620 ⁽²⁾	1	3	3	30	317
798+M2	Working cover cabinet 1 door with 2 compartments	28	28	-	-	1100 x 635 x 620 ⁽²⁾	-	2	2	30	194
794+M2	Tall cabinet 1 door with 2 compartments	55	55	-	-	1950 x 635 x 620 ⁽³⁾	2	2	2	30	304
794+M3	Tall cabinet 1 door with 3 compartments	30	30	-	30	1950 x 635 x 620 ⁽³⁾	3	3	option	30	307
794+M4	Tall cabinet 1 door with 4 compartments	22	22	22	22	1950 x 635 x 620 ⁽³⁾	-	4	4	30	320
795+M11	Tall cabinet 2 doors with 2 compartments	120	120	-	-	1950 x 1137 x 620 ⁽³⁾	6	2	option	30	477
795+M12	Tall cabinet 2 doors with 3 compartments	120	55	-	55	1950 x 1137 x 620 ⁽³⁾	5	3	2	30	486
795+M13	Tall cabinet 2 doors with 4 compartments	120	28	28	28	1950 x 1137 x 620 ⁽³⁾	6	4	option	30	489
795+M22	Tall cabinet 2 doors with 4 compartments	55	55	55	55	1950 x 1137 x 620 ⁽³⁾	4	4	4	30	497

(1) Depth with connecting sleeve at the back. Depth without sleeve: 520 mm
 (2) Depth with the connection sleeve at the back. Depth without sleeve: 620 mm
 (3) Height with the connection sleeve above. Height without sleeve: 1900 mm
⁽¹⁾ Compartments customization on request ⁽²⁾ Evenly distributed

Refer to the table of chemical incompatibilities and precautions for use, to validate the configuration of your cabinet according to your needs.

The manufacturer reserves the right to discontinue or change specifications or designs at any time without notice and without incurring obligations. 08/2019

Flammable cabinets

Corrosive cabinets

Toxic cabinets and multirisk

Pesticide range

Fume hoods, filtering cabinets - Ventilation

Containment and Cans

Anti-fire equipments and Files cabinets

Showers and first-aid equipments