

**Section 1. Identification****1.1 Product Identifier**

CHE1952

Product Name ETHANOLAMINE pure 500ml.

CAS Number 141-43-5

REACH Registration No 01-2119486455-28-XXXX

Molecular Formula  $\text{NH}_2\text{CH}_2\text{CH}_2\text{OH}$  = 61.08**1.2 Relevant identified uses of the substance or mixture & uses advised against**

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

**1.3 Supplier**

Scientific Laboratory Supplies

Unit 6, Foresters Avenue  
Fairham Business Park  
Fairham  
Nottingham  
NG11 2AF  
UNITED KINGDOM

Phone 0115 9821111

Fax 0115 9825275

Email sales@scientific-labs.com

**1.4 Emergency Telephone**(08:00-17:00) 0115 9821111  
(24hr) 112  
(Have this document to hand)**Section 2. Hazards Identification****2.1 Classification of the substance or mixture****Classification according to regulation 1272/2008/EC**

Skin corrosion/irritation, category 1B

Acute toxicity, category 4 (oral)

Acute toxicity, category 4 (dermal)

Acute toxicity, category 4 (inhalation)

Spec target organ tox - single, category 3

Hazard to aquatic environment, category 3

H314: Causes severe skin burns and eye damage.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

**2.2 Label elements****Labelling according to regulation 1272/2008/EC**

Signal word Danger

Hazard Pictograms



Hazard Statements Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

Precautionary Statements Avoid breathing dust / fume / gas / mist / vapours / spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

## Section 3. Composition

### 3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Ethanolamine	141-43-5	205-483-3	01-2119486455-28-XXXX	>99%	Skin Corr. 1B, Acute Tox. 4 (O), Acute Tox. 4 (D), Acute Tox. 4 (I), STOT SE 3 (I), Aquatic Chronic 3

## Section 4. First Aid

### 4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. If discomfort persists OBTAIN MEDICAL ATTENTION.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. In severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

## Section 5. Fire Fighting

### 5.1 Extinguishing media

Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards	Vapour-air mixtures are explosive.
---------	------------------------------------

### 5.3 Advice for firefighters

Advice for firefighters	Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.
-------------------------	--

## Section 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.
---------------------	---

### 6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

Minor Spillage Wash area down with copious amounts of water.

### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

## Section 7. Storage & Handling

### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

### 7.3 Specific end use(s)

See section 1.2.

## Section 8. Workplace Exposure & Personal Protection

### 8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr TWA)		Short Term 15min period	
Ethanolamine	141-43-5	>99%	1.0 ppm	2.5 mg/m-3	3.0 ppm	7.6 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

### 8.2 Exposure controls

Respiratory Protection Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

## Section 9. Physical & Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Slight ammoniacal odour.

pH 12.1@0.1%

Boiling Point 170°C

Melting Point 4°C

Flash Point 92.5°C (Closed cup)

Upper Flammable Limit Not applicable

Lower Flammable Limit Not applicable

Auto Ignition 410°C

Explosive Properties Slight.

Oxidising Properties No.

Vapour Pressure 0.5mbar @ 20°C

Relative Density	1.0155 @ 20°C
Water Solubility	Completely miscible in water.

## 9.2 Other information

No data available.

## Section 10. Stability & Reactivity

10.1 Reactivity	No data available.
10.2 Chemical Stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	No data available.
10.4 Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5 Incompatible Materials	Mineral acids. Strong oxidising agents.
10.6 Hazardous Decomposition Products	Burning will produce toxic fumes of NO <sub>x</sub> , carbon monoxide and/or carbon dioxide.

## Section 11. Toxicological Information

### 11.1 Information on toxicological effects

Eyes	The liquid or concentrated vapour will cause severe irritation and corneal damage.
Skin	Cause severe irritation and burns to the skin. May be absorbed through the skin.
LD50 Skin	1025mg/kg Rabbit
Ingestion	Harmful if swallowed. Causes burns.
LD50 Oral	1720mg/kg Rat
Inhalation	Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and respiratory tract. High concentrations of vapour may cause loss of appetite, dizziness, fatigue and nausea. Liver and kidney damage may also occur. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
LD50 Inhalation	11.0mg/l Acute toxicity estimate
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	Not teratogenic but high doses have caused maternal and foetal toxicity.

## Section 12. Ecological

12.1 Toxicity	Harmful to aquatic life with long lasting effects. Readily bio-degraded in the environment.
LC50 Algal	Not available
LC50 Crustacea	65mg/l Daphnia magna (48 hours)
LC50 Fish	227mg/l Fathead Minnow (96 hours)
12.2 Persistence and degradability	No data available.
12.3 Bioaccumulative potential	No data available.
12.4 Mobility in soil	No data available.
12.5 Results of PBT & vPvB assessment	Assessment not required.
12.6 Other adverse effects	None known at present.

## Section 13. Disposal Considerations

### 13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

## Section 14. Transport Information

14.1 UN Number	2491
14.2 Proper Shipping Name	Ethanolamine
14.3 Transport classes	
UN classification	8
Subsidiary hazard(s)	None
Transport category	3
ADR Hazard ID	80
Tunnel Restriction Code	E
14.4 Packing Group	III
14.5 Environment hazards	See section 12.
14.6 Special precautions for user	No special precautions required.
14.7 Transport in bulk	Not transported in bulk.



## Section 15. Regulatory Information

### 15.1 Safety, health and environment regulations specific for substance/mixture.

#### Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Skin corrosion/irritation, category 1B; Acute toxicity, category 4 (oral); Acute toxicity, category 4 (dermal); Acute toxicity, category 4 (inhalation); Spec target organ tox - single, category 3; Hazard to aquatic environment, category 3

Signal word Danger

Hazard Pictograms



Hazard Statements H332, H312, H302, H314, H335, H412  
Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

Precautionary Statements P261, P271, P264, P270, P301+P312, P304+P340  
Avoid breathing dust / fume / gas / mist / vapours / spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

### 15.2 Chemical safety assessment

Assessment not required.

## Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supersedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 16 September 2024

