Scientific Laboratory Supplies - Safety Data Sheet CHE2102

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 2.1 Revision date: 16 April 2021
Date printed: 16 September 2024

Section 1. Identification

1.1 Product Identifier CHE2102

Product Name HEXAN-1-OL pure 500ml.

CAS Number 111-27-3
REACH Registration No 01-2119487967-12-XXXX

Molecular Formula $CH_3(CH_2)_4CH_2OH$ =102.18

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Scientific Laboratory Supplies

Unit 6, Foresters Avenue
Fairham Business Park
Fairham
Nottingham
NG11 2AF
UNITED KINGDOM

Phone 0115 9821111
Fax 0115 9825275
Email sales@scientific-labs.com

1.4 Emergency Telephone (08:00-17:00) 0115 9821111
(24hr) 112
(Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 3	H226: Flammable liquid and vapour.
Acute toxicity, category 4 (oral)	H302: Harmful if swallowed.
Acute toxicity, category 4 (dermal)	H312: Harmful in contact with skin.
Serious eye damage/irritation, category 2	H319: Causes serious eye irritation.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word Warning

Hazard Pictograms

Hazard Statements Flammable liquid and vapour. Causes serious eye irritation. Harmful if swallowed. Harmful in contact with skin.

Precautionary Statements	Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Wash thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF ON SKIN: Wash with plenty of soap and water.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Hexan-1-ol	111-27-3	203-852-3	01-2119487967-12-XXXX	>95%	Flam. Liq. 3,Acute Tox. 4 (O),Acute Tox. 4 (D),Eye Irrit. 2

Section 4. First Aid

4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately avoiding contamination of unaffected areas.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards	Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters	Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

6.2 Environmental precautions

Enviromental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr TWA)		Short Term 15min period)	
Hexan-1-ol	111-27-3	>95%	-	-	-	-

Exposure data source(s) No occupational exposure data currently available.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Clear colourless liquid.
Odour	Pungent.
pH	Not applicable
Boiling Point	157°C Approx.
Melting Point	-52°C
Flash Point	57°C (Closed cup)
Upper Flammable Limit	7.7%
Lower Flammable Limit	1.2%
Auto Ignition	293°C
Explosive Properties	Slight.
Oxidising Properties	No.
Vapour Pressure	0.75mmHg @ 20°C
Relative Density	0.8250

Water Solubility	Insoluble in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Acids. Strong oxidising agents.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes	The liquid may cause severe irritation and corneal damage. High concentrations of vapour may cause severe irritation.
Skin	Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Liquid can be absorbed through intact skin. Very significant absorbtion can lead to collapse and may even prove fatal.
LD50 Skin	1500 - 2000mg/kg Rabbit
Ingestion	Harmful if swallowed. Ingestion may cause central nervous system depression, leading to unconsciousness. Symptoms may include salivation, thirst, difficulty in swallowing, pain, shock and vomiting.
LD50 Oral	720mg/kg Rat
Inhalation	Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and respiratory tract. High concentrations of vapour may effect the central nervous system acting as a narcotic.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	None identified.

Section 12. Ecological

12.1	Toxicity	Readily bio-degraded in the environment.
	LC50 Algal	11.3mg/l Green algae (72 hours)
	LC50 Crustacea	201mg/l Daphnia magna (24 hours)
	LC50 Fish	97mg/l Fathead Minnow (96 hours)
12.2	Persistence and degradability	Readily bio-degraded in the environment.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods	Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.
Contaminated Packaging	Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1	**UN Number**	2282
14.2	**Proper Shipping Name**	Hexanols
14.3	**Transport classes**	
	UN classification	3
	Subsidiary hazard(s)	None
	Transport category	3
	ADR Hazard ID	30
	Tunnel Restriction Code	D/E
14.4	**Packing Group**	III
14.5	**Environment hazards**	See section 12.
14.6	**Special precautions for user**	No special precautions required.
14.7	**Transport in bulk**	Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification	Flammable liquid, category 3; Acute toxicity, category 4 (oral); Acute toxicity, category 4 (dermal); Serious eye damage/irritation, category 2
Signal word	Warning
Hazard Pictograms	
Hazard Statements	H226, H319, H302, H312 Flammable liquid and vapour. Causes serious eye irritation. Harmful if swallowed. Harmful in contact with skin.
Precautionary Statements	P210, P233, P240, P243, P264, P305+P351+P338, P302+P352 Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Wash thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF ON SKIN: Wash with plenty of soap and water.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.1 (Supercedes revision 2.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 16 September 2024