Scientific Laboratory Supplies - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1

Revision date: Date printed: 16 April 2021 16 September 2024

CHE2784

Section 1. Identification

1.1	Product Identifier	CHE2784
	Product Name	PETROLEUM SPIRIT 100/120 pure 1L.
	CAS Number REACH Registration No	8032-32-4 01-2119473851-33-XXXX

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

Scientific Laboratory Supplies



Unit 6, Foresters Avenue Fairham Business Park Fairham Nottingham NG11 2AF UNITED KINGDOM

	Phone	0115 9821111	
	Fax	0115 9825275	
	Email	sales@scientific-	abs.com
1.4	Emergency Telephone	(08:00-17:00)	0115 9821111
		(24hr)	112

(24hr) (Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 Skin corrosion/irritation, category 2 Reproductive toxicity, category 2 Spec target organ tox - single, category 3 Aspiration hazard, category 1 Hazard to aquatic environment, category 2

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word

Danger

Hazard Pictograms



H225: Highly flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

H361: Suspected of damaging fertility or the unborn child.

H304: May be fatal if swallowed and enters airways.

H411: Toxic to aquatic life with long lasting effects.

H315: Causes skin irritation.

Hazard Statement	ts	Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Suspected of damaging fertility or the unborn child.
Precautionary Sta	tements	Obtain special instructions before use. Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice/attention. Store in a well ventilated place. Keep cool. Avoid release to the environment.
Supplemental Haz Information (EU)		Repeated exposure may cause skin dryness or cracking.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Mixed hydrocarbon solvent 8032-32-4 232-453-7		01-2119473851-33-XXXX	>99.5%	Flam. Liq. 2,Skin Irrit. 2,Repr. 2,STOT SE 3 (D),Asp. Tox. 1,Aquatic Chronic 2	

Section 4. First Aid

4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.
Skin	Thoroughly wash off skin with soap and water. Remove contaminated clothing immediately and wash before re- use. In severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media	Water spray, foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture Hazards

Vapour-air mixtures are explosive.

5.3 Advice for firefighters Advice for firefighters

Personal Protection

Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

6.2 Environmental precautions

Enviromental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local
	Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents. Large quantities must be stored in accordance with the Petroleum Spirits Act.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8hr	TWA)	Short Term 15	min period)
Mixed hydrocarbon solvent	8032-32-4	>99.5%	240.0 ppm	-	-	-

Exposure data source(s)

IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Clear colourless liquid.
Odour	Characteristic.
pH	Not applicable
Boiling Point	102°C
Melting Point	-30°C
Flash Point	-7°C (Closed cup)
Upper Flammable Limit	8%
Lower Flammable Limit	0.9%

Scientific Laboratory Supplies - Safety Data Sheet

Auto Ignition Explosive Properties Oxidising Properties Vapour Pressure Relative Density Water Solubility 230°C Severe in confined spaces. No. 40mmHg @ 20°C 0.7270 Insoluble in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Strong oxidising agents.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes	Both the vapour and liquid will, act as an eye irritant. Repeated exposure to the vapours can lead to reversible corneal changes and conjunctivitis
Skin	The liquid is mildly irritating to the skin. Repeated or prolonged contact may defat the skin producing irritation and dermatitis.
LD50 Skin	>2920mg/kg Rat
Ingestion	Ingestion will cause causes damage to stomach and intestinal linings. May be fatal if swallowed and enters airways.
LD50 Oral	>5840mg/kg Rat
Inhalation	Exposure to vapour concentrations above the occupational exposure limits will cause narcosis. Prolonged exposure to vapour concentrations above the occupational exposure limits will cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may produce central nervous system depression and unconsciousness.
LD50 Inhalation	>23300mg/l Rat (4 hours)
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	No information found.

Section 12. Ecological

12.1	Toxicity	Moderately toxic to mammals, fish and bacteria.
	LC50 Algal	10-30mg/l Algae (72 hours)
	LC50 Crustacea	4.6 - 10.0mg/l Daphnia (48 hours)
	LC50 Fish	3-10mg/l Fish (96 hours)
12.2	Persistence and degradability	No data available.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

Scientific Laboratory Supplies - Safety Data Sheet

Ref: CHE2784

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1	UN Number	1268
14.2	Proper Shipping Name	Petroleum distillates, N.O.S.
14.3	Transport classes UN classification Subsidiary hazard(s) Transport category ADR Hazard ID Tunnel Restriction Code	3 None 2 33 D/E
14.4	Packing Group	Π
14.5	Environment hazards	See section 12.
14.6	Special precautions for user	No special precautions required.
14.7	Transport in bulk	Not transported in bulk.
a	1 15 D	

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE) Classification Flammable liquid, category 2; Skin corrosion/irritation, category 2; Reproductive toxicity, category 2; Spec target organ tox - single, category 3; Aspiration hazard, category 1; Hazard to aquatic environment, category 2 Signal word Danger Hazard Pictograms Hazard Statements H225, H315, H336, H304, H411, H361 Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Suspected of damaging fertility or the unborn child. P201, P210, P280, P308+P313, P403+P235, P273 Precautionary Statements Obtain special instructions before use. Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice/attention. Store in a well ventilated place. Keep cool. Avoid release to the environment. Supplemental Hazard EUH066 Information (EU) Repeated exposure may cause skin dryness or cracking.

15.2 Chemical safety assessment Assessment not required.

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 16 September 2024

Copyright: 2024 Scientific Laboratory Supplies