# Scientific Laboratory Supplies - Safety Data Sheet

**CHE3118** 

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1 Revision date: 16 April 2021
Date printed: 16 September 2024

## Section 1. Identification

1.1 Product Identifier CHE3118

Product Name PROPAN-2-OL pure 500ml.

CAS Number 67-63-0

REACH Registration No 01-2119457558-25-XXXX

Molecular Formula (CH<sub>3</sub>)<sub>2</sub> CHOH =60.10

### 1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

**1.3 Supplier** Scientific Laboratory Supplies



Unit 6, Foresters Avenue Fairham Business Park

Fairham Nottingham NG11 2AF

UNITED KINGDOM

Phone 0115 9821111 Fax 0115 9825275

Email sales@scientific-labs.com

**1.4 Emergency Telephone** (08:00-17:00) 0115 9821111

(24hr) 112

(Have this document to hand)

## Section 2. Hazards Identification

### 2.1 Classification of the substance or mixture

### Classification according to regulation 1272/2008/EC

Flammable liquid, category 2
H225: Highly flammable liquid and vapour.
Serious eye damage/irritation, category 2
H319: Causes serious eye irritation.
Spec target organ tox - single, category 3
H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

### Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms





Hazard Statements Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

**Precautionary Statements** 

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store in a well ventilated place. Keep cool.

## **Section 3. Composition**

#### 3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Propan-2-ol	67-63-0	200-661-7	01-2119457558-25-XXXX	>99.7%	Flam. Liq. 2,Eye Irrit. 2,STOT SE 3 (D)

### Section 4. First Aid

#### 4.1 Description of first aid measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL

ATTENTION.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use.

Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If Inhalation

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen Ingestion

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the

recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

## **Section 5. Fire Fighting**

#### 5.1 Extinguishing media

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

## 5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

## Section 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate Personal Protection

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

## 6.2 Environmental precautions

Enviromental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

#### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

## Section 7. Storage & Handling

#### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

#### 7.3 Specific end use(s)

See section 1.2.

## Section 8. Workplace Exposure & Personal Protection

#### 8.1 Control parameters

l	Component	CAS No	Concentration	tration Workplace Exposure Limits			
				Long Term (8hr TWA)		Short Term 15min period)	
1	Propan-2-ol	67-63-0	>99.7%	400.0 ppm	999.0 mg/m-3	500.0 ppm	1250.0 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

## Section 9. Physical & Chemical Properties

#### 9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.
Odour Fresh and characteristic.

pH Not applicable
Boiling Point 82.2°C
Melting Point -89.5°C

Flash Point 12°C (Closed cup)

Upper Flammable Limit 12% Lower Flammable Limit 2% Auto Ignition 460°C

Explosive Properties Moderate/severe in confined spaces.

Oxidising Properties No.

Vapour Pressure 31.2mmHg @ 20°C

Relative Density 0.7863

Water Solubility Completely miscible in water.

#### 9.2 Other information

No data available.

## Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

Possibility of hazardous No data available.

reactions

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Strong oxidising agents. Nitric acid. Silver nitrate, potassium perchlorate, chromyl chloride, chromium trioxide

and permanganic acid. Peroxides, potassium permanganate, sodium, potassium, platinum, potassium tertiary

Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

**Products** 

## Section 11. Toxicological Information

### 11.1 Information on toxicological effects

Eyes Both the vapour and liquid may, be irritating to the eyes. High concentrations of vapour may produce conjunctival

irritation and corneal damage.

Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Many of the effects typical Skin

of the vapour can result from absorbtion through the skin.

LD50 Skin 12800mg/kg Rabbit

Ingestion Low order of acute toxicity. Ingestion of large amounts will produce central nervous system depression. Ingestion

will cause similar effects to inhalation.

LD50 Oral 5840mg/kg Rat

Inhalation Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and

respiratory tract. High concentrations of vapour may effect the central nervous system acting as a narcotic.

LD50 Inhalation Not available TCLo Not available

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects None identified.

## Section 12. Ecological

12.1 Toxicity LC50, 96hr, fish 9600 mg/l; EC50, 24hr, Daphnia >10000 mg/l; Readily bio-degraded in the environment.

LC50 Algal Not available LC50 Crustacea See results above. LC50 Fish See results above. 12.2 Persistence and See results above. degradability

12.3 Bioaccumulative potential No data available. 12.4 Mobility in soil No data available.

Results of PBT & vPvB

assessment

Assessment not required.

12.6 Other adverse effects None known at present.

# Section 13. Disposal Considerations

### 13.1 Waste treatment methods

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of Disposal Methods

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

## Section 14. Transport Information

14.1 UN Number 1219

14.2 Proper Shipping Name Isopropanol

14.3 Transport classes


UN classification Subsidiary hazard(s) None Transport category 2 ADR Hazard ID 33 **Tunnel Restriction Code** D/E Ħ

14.4 Packing Group

14.5 Environment hazards See section 12.

14.6 Special precautions for No special precautions required.

14.7 Transport in bulk Not transported in bulk.



15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 2; Serious eye damage/irritation, category 2; Spec target organ tox - single, category 3

Signal word Danger

Hazard Pictograms





Hazard Statements H225, H319, H336

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary Statements P210, P280, P305+P351+P338, P337+P313, P303+P361+P353, P403+P235

> Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store in a well

ventilated place. Keep cool.

### 15.2 Chemical safety assessment

Assessment not required.

## Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 16 September 2024

Page 5 of 6 Scientific Laboratory Supplies - Safety Data Sheet Ref: CHE3118

Copyright: 2024 Scientific Laboratory Supplies