Scientific Laboratory Supplies - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1 Revision date: 16 April 2021 Date printed: 16 September 2024

Section 1. Identification

1.1 Product Identifier CHE3640

Product Name STYRENE pure 500ml.

CAS Number 100-42-5

REACH Registration No A registration number is not available as the substance or its uses are exempt, the

annual tonnage does not require a registration or the registration is envisaged for a

later date.

Molecular Formula C, H, CH: CH₂ =104.15

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Scientific Laboratory Supplies

SCIENTIFIC LABORATORY SUPPLIES

Unit 6, Foresters Avenue Fairham Business Park

Fairham Nottingham NG11 2AF

UNITED KINGDOM

Phone 0115 9821111 Fax 0115 9825275

Email sales@scientific-labs.com

1.4 Emergency Telephone (08:00-17:00) 0115 9821111

(24hr) 112

(Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 3 H226: Flammable liquid and vapour. Skin corrosion/irritation, category 2 H315: Causes skin irritation. Acute toxicity, category 4 (inhalation) H332: Harmful if inhaled.

Serious eye damage/irritation, category 2 H319: Causes serious eye irritation.

Reproductive toxicity, category 2 H361: Suspected of damaging fertility or the unborn child.

Spec target organ tox - repeat, category 1 H372: Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms







Flammable liquid and vapour. Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Hazard Statements

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Do not breathe dust / fume / gas / mist /

vapours / spray. Wear protective gloves / protective clothing / eye protection / face protection. Use only outdoors or in a well-ventilated area. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses

if present and easy to do and continue rinsing.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Styrene	100-42-5	202-851-5			Flam. Liq. 3,Skin Irrit. 2,Acute Tox. 4 (I),Eye Irrit. 2,Repr. 2,STOT RE 1

Section 4. First Aid

4.1 Description of first aid measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL

ATTENTION URGENTLY.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. If

discomfort persists OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen Ingestion

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the

recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

4.2 Most important symptoms and effects, both acute & delayed.

Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Alcohol resistant foam, dry powder, carbon dioxide or vaporising liquid. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow

general use of area until it is safe to do so. Beware: vapour is heavier than air and will tend to accumulate at low

spots.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

detergent and copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with detergent and copious

amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits				
			Long Term (81	Long Term (8hr TWA)		Short Term 15min period)	
Styrene	100-42-5	>99%	100.0 ppm	250.0 mg/m-3	430.0 ppm	1080.0 mg/m-3	

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Aromatic. pH Not applicable Boiling Point 145.2°C
Melting Point -31.2°C

Flash Point 32°C (Closed cup)

Upper Flammable Limit 8.9% Lower Flammable Limit 1.1% Auto Ignition 490°C

Explosive Properties Severe in confined spaces.

Oxidising Properties No.

Vapour Pressure 6.5mmHg @ 20°C

Relative Density 0.9030 Water Solubility Negligible.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions but can polymerise if the storage time and temperature is exceeded.

10.3 Possibility of hazardous No data available.

reactions

10.4 Conditions to Avoid

Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Strong oxidising agents. Mineral acids. Alkalis. Free radical formers eg peroxides. Phosphorous pentoxide.

Ferrous chloride and other metal halides.

10.6 Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Products

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Both the vapour and liquid are, irritating to the eyes.

Skin Repeated or prolonged contact may defat the skin producing irritation and dermatitis.

LD50 Skin >2000mg/kg Rat

Ingestion Low order of acute toxicity.

LD50 Oral >6000mg/kg Rat

Inhalation Exposure to vapour concentrations above the occupational exposure limits may lead to tiredness, loss of memory,

prolonged reaction time and impaired manual dexterity. High concentrations of vapour may lead to pronounced

dizziness, nausea, loss of appetite and co-ordination.

LD50 Inhalation >12000mg/m3 Rat

TCLo Not available

Carcinogenicity No conclusive evaluation of its carcinogenic properties has been made.

Mutagenicity May be a mutagen.

Reproductive Effects Evidence of reproductive effects. May damage the unborn child.

Section 12. Ecological

12.1 Toxicity Moderately toxic to mammals, fish and bacteria.

LC50 Algal 1.4mg/l Green algae (72 hours)

LC50 Crustacea 4.7mg/l Daphnia magna (96 hours)
LC50 Fish 32mg/l Fathead Minnow (96 hours)

12.2 Persistence and No data available.

degradability

12.3 Bioaccumulative potential No data available.

12.4 Mobility in soil No data available.

12.5 Results of PBT & vPvB

assessment

Assessment not required.

12.6 Other adverse effects

None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number 2055

14.2 Proper Shipping Name Styrene monomer, stabilized

14.3 Transport classes

UN classification 3 None Subsidiary hazard(s) Transport category 3 ADR Hazard ID 39 D/E **Tunnel Restriction Code**

14.4 Packing Group

14.5 Environment hazards See section 12.

14.6 Special precautions for

user

No special precautions required.

14.7 Transport in bulk Not transported in bulk.



15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 3; Skin corrosion/irritation, category 2; Acute toxicity, category 4 (inhalation); Serious

eye damage/irritation, category 2; Reproductive toxicity, category 2; Spec target organ tox - repeat, category 1

Signal word Danger

Hazard Pictograms







Hazard Statements H226, H332, H319, H315, H361, H372

> Flammable liquid and vapour. Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements P210, P260, P280, P271, P305+P351+P338

> Keep away from heat / sparks/open flames/hot surfaces - No smoking. Do not breathe dust / fume / gas / mist / vapours / spray. Wear protective gloves / protective clothing / eye protection / face protection. Use only outdoors or in a well-ventilated area. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses

if present and easy to do and continue rinsing.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 16 September 2024

Copyright: 2024 Scientific Laboratory Supplies