# Scientific Laboratory Supplies - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1

Revision date: Date printed: 16 April 2021 16 September 2024

**CHE387(** 

## Section 1. Identification

1	Product Identifier	CHE3870
	Product Name	WANKLYN'S SOAP SOLUTION 2.5L.
	CAS Number REACH Registration No	Mixture A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.

#### 1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

1.1

Scientific Laboratory Supplies



Unit 6, Foresters Avenue Fairham Business Park Fairham Nottingham NG11 2AF UNITED KINGDOM

.4	Emergency Telephone	(08:00-17:00)	0115 9821111
	Fax Email	0115 9825275 sales@scientific-la	bs.com
	Phone	0115 9821111	

1.7	Emergency receptione	(00.00 - 17.00)	0115 7621111
		(24hr)	112
		(Have this docum	ent to hand)

## Section 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

#### Classification according to regulation 1272/2008/EC

Flammable liquid, category 3 Serious eye damage/irritation, category 2 H226: Flammable liquid and vapour. H319: Causes serious eye irritation.

#### 2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word

Warning





Hazard Statements

Flammable liquid and vapour. Causes serious eye irritation.

Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing.

## Section 3. Composition

#### 3.2 Mixtures

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Ethanol	64-17-5	200-578-6	01-2119457610-43-XXXX	57%	Flam. Liq. 2,Eye Irrit. 2
Methanol	67-56-1	200-659-6	01-2119433307-44-XXXX	1.5%	Flam. Liq. 2, Acute Tox. 3 (O), Acute Tox. 3 (D), Acute Tox. 3 (I), STOT SE 1
Potassium hydroxide	1310-58-3	215-181-3	01-2119487136-33-XXXX	0.2%	Skin Corr. 1A, Acute Tox. 4 (O)

## Section 4. First Aid

#### 4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

#### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

### **Section 5. Fire Fighting**

#### 5.1 Extinguishing media

Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
TT 1/11 N/ 11	

Unsuitable Media Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Vapour-air mixtures are explosive.

#### 5.3 Advice for firefighters

Hazards

Advice for firefighters

Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

## Section 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

#### **6.2 Environmental precautions**

Enviromental

Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

#### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

#### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

## Section 7. Storage & Handling

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

#### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition.

#### 7.3 Specific end use(s)

See section 1.2.

## Section 8. Workplace Exposure & Personal Protection

#### 8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8h	r TWA)	Short Term 15mi	n period)
Ethanol	64-17-5	57%	1000.0 ppm	1920.0 mg/m-3	-	-
Methanol	67-56-1	1.5%	200.0 ppm	266.0 mg/m-3	250.0 ppm	333.0 mg/m-3
Potassium hydroxide	1310-58-3	0.2%	-	-	-	2.0 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

#### 8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

### Section 9. Physical & Chemical Properties

#### 9.1 Information on basic physical and chemical properties

Clear colourless to pale yellow liquid.
Fresh and characteristic.
7 @ 20°C
81°C
-42°C
22°C (Closed cup)
19%
3.3%
363°C
Moderate/severe in confined spaces.
No.
59mmHg @ 20°C

Scientific Laboratory Supplies - Safety Data Sheet

Ref: CHE3870

Relative Density Water Solubility 0.9000 Completely miscible in water.

#### 9.2 Other information

No data available.

# Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Strong oxidising agents.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

## Section 11. Toxicological Information

#### **11.1 Information on toxicological effects**

Eyes	The liquid will cause conjunctival irritation and corneal damage. High concentrations of vapour may be irritating to the eyes.
Skin	Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Unlikely to be absorbed across the skin in harmful amounts.
LD50 Skin	Not available
Ingestion	Low order of acute toxicity. Fatal dose in man 300-400ml. Ingestion of large amounts will produce central nervous system depression. Symptoms may include nausea, vomiting muscular incoordination and loss of consciousness. Aspiration during swallowing or vomiting may injure lungs.
LD50 Oral	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and respiratory tract. High concentrations of vapour may produce central nervous system depression and unconsciousness. Symptoms will be similar to those following ingestion.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	Some evidence for foetoxicity and tetragenecity has been observed in experimental animals treated with high doses of ethanol during gestation.
Other Information	Contains methanol. This will not constitute a special problem since ethanol is preferentially metabolised. Chronic intoxication may however produce damage to the optic nerve.

# Section 12. Ecological

12.1	Toxicity	Ethanol is readily biodegradable after 15 days in non-acclimated fresh water. 75% biodegradability occurs after 20 days in salt water.
	LC50 Algal	Not available
	LC50 Crustacea	Not available
	LC50 Fish	Not available
12.2	Persistence and degradability	No data available.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

Scientific Laboratory Supplies - Safety Data Sheet

Ref: CHE3870

## Section 13. Disposal Considerations

#### 13.1 Waste treatment methods

**Disposal Methods** 

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

**Contaminated Packaging** Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

### Section 14. Transport Information

14.1	UN Number	1170
14.2	Proper Shipping Name	Ethanol
14.3	Transport classes UN classification Subsidiary hazard(s) Transport category ADR Hazard ID Tunnel Restriction Code	3 None 2 33 D/E
14.4	Packing Group	II
14.5	Environment hazards	See section 12.
14.6	Special precautions for user	No special precautions required.
14.7	Transport in bulk	Not transported in bulk.

## Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)		
Classification	Flammable liquid, category 3; Serious eye damage/irritation, category 2	
Signal word	Warning	
Hazard Pictograms		
Hazard Statements	H226, H319 Flammable liquid and vapour. Causes serious eye irritation.	
Precautionary Statements	P233, P280, P303+P361+P353, P305+P351+P338 Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing.	

#### 15.2 Chemical safety assessment

Assessment not required.

## Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 16 September 2024

Copyright: 2024 Scientific Laboratory Supplies