

ID-Nr. 30606-001 Model SL.196.120.MV



Dimensions	
Width (external)	1197.00 mm
Depth (external)	603.00 mm
Height (external)	1965.00 mm
Width (internal)	485.00 mm
Depth (internal)	570.00 mm
Height (internal)	1869.00 mm
The available internal dimensions can vary depending on the interior equipment package	

The available internal dimensions can vary depending on the interior equipment package.

Weight / Load	
Weight without interior equipment	215 kg
Distributed load	240.00 kg/m²
Maximum load	300 kg
Ventilation	
Extraction air	75 DN
Recom. exhaust air quantity 30 times	16 m³/h
Differential pressure (30 times air change)	56 Pa
Minimum exhaust air quantity 10 times	10 m³/h
Differential pressure (10 times air change)	56 Pa
Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	light grey
Door / Drawer surface finish	plain
General Information	
Number of doors	2

Depth with open doors Customs tariff number









Cabinet for acids and alkalis SL-CLASSIC Model SL.196.120.MV, light grey (RAL 7035)

Safe and approved storage of aggressive, non flammable hazardous materials in working areas

Function / construction:

- Robust construction and longevity: cabinet body made of powder-coated sheet steel, safety elements assembled outside the storage compartment for increased protection against corresion.
- **Two in one:** two hermetically separated storage compartments allow the isolated storage of acids and bases in one cabinet
- No unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- **ventilation:** integrated metal-free air ducts ready for connection to a technical exhaust system with only one extraction air inlet

Front view Side view





