



Information for customer: FROSTERS® Gloves

GLOVE DESCRIPTION

The outer layer, of royal blue, woven, polyamide, has a waterproof coating to resist condensed water on cold surfaces. The middle layer is of special polyolefin/polyester micro fibre, which is almost twice as effective in thermal insulation as a similar thickness of down. This minimises heat transfer without being so thick as to be cumbersome. The inner layer is of cotton for comfortable wear.

Stockcode	Style Ref	Description	Size EN 420
2720000011	V8659	GLO/CMS	8
2720000012	V8659	GLO/CMM	9
2720000013	V8659	GLO/CML	10
2720000014	V8659	GLO/CMXL	11
2720000021	V8659A	GLO/CMES	8
2720000022	V8659A	GLO/CMEM	9
2720000023	V8659A	GLO/CMEL	10
2720000024	V8659A	GLO/CMEXL	11
2720000031	V8659EX	GLO/CMS/EX	8
2720000032	V8659EX	GLO/CMM/EX	9
2720000033	V8659EX	GLO/CML/EX	10
2720000034	V8659EX	GLO/CMXL/EX	11
2799990011	V0658	GLO/CMS/KW	8
2799990012	V0658	GLO/CMM/KW	9
2799990013	V0658	GLO/CML/KW	10
2799990014	V0658	GLO/CMXL/KW	11
2799990051	V8659/KW	GLO/CMS/KW	8
2799990052	V8659/KW	GLO/CMM/KW	9
2799990053	V8659/KW	GLO/CML/KW	10
2799990054	V8659/KW	GLO/CMXL/KW	11

Gloves are made to EN 420:2003 +A1:2009 sizes.



*Warning: These gloves may lose their insulative properties when wet.

Gloves can be used under normal climatic conditions.

Gloves can be used up to 5 years after the date of manufacture if stored correctly. Store in original packaging. Store away from direct sunlight to maintain the optimum properties. This glove series satisfies the basic requirements of the PPE Directive in being innocuous/free from nuisance factors, ergonomic and breathable. Conditions of use are not simulated by the test results and as such service life cannot be specified. Results should be used for guidance in initial selection.

MARKING

Each packet shall be labelled / contain the appropriate marking with regards to the amount, type, size, manufacturer, performance levels and CE mark. Labels on the gloves shall contain similar information. This information will be provided in the minimum resale quantity.

Warning:

Care Instructions: In the event of mild contamination, gloves may be rinsed in water and allowed to drip dry in ambient temperatures.

TD-1046

Test Results			
Abrasion resistance:	2	EN388:2016	2X2X
Tear resistance:	2	EN388:2016	
Contact cold:	2	EN511:2006	2X**
Convective cold:	2	EN511:2006	
Flexibility:	Pass	EN511:2006	
Water Resistance	N/A	EN511:2006**	
Additional Information			
Water Penetration	162-196 Kpa	EN20811:2018	

(**The water resistance test does not apply to the glove styles they should not be immersed in liquids as this may lead to a reduction in the insulative properties of the gloves.)

These gloves have been specifically designed for use when handling non-flammable liquid gas and the user should not be exposed to the low temperatures for sustained periods. Gloves should not be worn where there is a risk of entanglement with moving parts of machines. The whole glove performance may not reflect the performance of the outermost layer. Damaged gloves will not offer the same level of performance and should be replaced.

INTERMEDIATE SAFETY CATERGORY

Gloves are designed to protect hands in the working environment in accordance with EN388:2016, EN420:2003+A1:2009 & EN511:2006. When selecting a glove based on risk analysis it should be understood that the protection is limited to the risk level and standards mentioned above. The EU type examination was carried out ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: performed the type-examination. The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body.. is subject to ongoing surveillance by SGS Fimko Oy, P.O. Box 30 (Särkiniementie 3), 00211 HELSINKI, Finland. Their notified body number is 0598.. None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

WARNINGS:

Guidance on maximum permissible exposure time to cold temperatures is given in Annex B of EN 511:2006. Test results apply to the gloves in the as received condition and may differ if cleaned. Overall classification may not reflect the performance of only the outermost layer. These gloves are not suitable for protection against sharply pointed objects such as hypodermic needles.

CARE / MAINTENANCE

Cleaning and disinfection is not intended for these gloves. Both new and used gloves should be thoroughly inspected before and after use, especially after cleaning treatment, and before being worn to ensure no damage is present. Damaged gloves should not be worn and should be disposed of. Wet or contaminated gloves should not be used. Dirty gloves may not provide the same level of protection as that shown. Gloves should not be left in a contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from the hands. Excess contaminant should first be removed, e.g. loose dirt can be brushed off with a soft brush. The gloves may be de-contaminated with mild detergent solution, then rinsed with clean water and allowed to dry naturally, ideally with some air movement. When the contaminant is not removable or presents a potential hazard, it is advisable to ease left and right hand gloves off alternately using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands. Washing is not recommended.

Do not wring. Do not tumble dry. Do not use bleach. Gloves may be rinsed in water and allowed to drip dry in ambient temperatures. Reshape whilst still damp.

Warning:

PACKING AND STORAGE

Can be used under normal climatic conditions. Gloves shall be wrapped in polymeric packaging.

Gloves can be used up to five years after date of supply if stored correctly. Store in original packaging. Gloves should be ideally stored in a cool dry place away from direct sunlight at ambient temperatures (between 5°C and 25°C) in a dry well ventilated area in original packaging to maintain the optimum properties of the glove. The gloves are packed in bundles, along with this leaflet. This bundle is suitable for transportation and storage.

OBSOLESCENCE

Stored correctly, the gloves' physical properties will not change for up to five years.

GENERAL The quality systems used to manufacture the gloves is in compliance with ISO 9001:2015.

PLEASE NOTE The information contained here is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection; however, it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitable for the intended use

EU DECLARATION

Scilabub Limited declares that the new PPE as described in the TD 1046 technical specification for Frosterl gloves are in conformity with provisions of Council Regulations (EU) 2016/425 and with the national standard transposing harmonised standard No :BS EN 388:2016, BS EN 511:2006, BS EN 420:2003, and identical to the PPE which is the subject of the EU certificate. No: LECF00373976, issued by: ITS Testing Services, Centre Court, Meridian Business Park, Leicester, LE19 1WD, UK., notified body number is 0362: who performed the type-examination. The notified body Intertek Italia S.p.A. Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy NB 2575, now owns this document, and it is valid under this notified body and is subject to the quality procedures under the supervision of the notified body SGS Fimko Oy, P.O. Box 30 (Särkiniementie 3), 00211 HELSINKI, Finland. Their notified body number is 0598.

Done at : Scilabub Limited , 9 Huntingdon Court, Measham, Derbyshire, DE12 7NQ, UK

Signature: Mr M.Gee Director

Further copies of this information and declarations of conformity are available on request from:

9 Huntingdon Court, Measham, Derbyshire, DE12 7NQ, UK.
T: +44 (0) 1530 279996 <http://www.scilabub.com> email: sales@scilabub.com