



designed for scientists



## S 25 EC - T - C - 25 F Dispersing tool

/// Data Sheet

The dispersing tool S 25 EC-T-C-25F is particularly suitable for dispersing applications in cosmetics. The integrated temperature sensor enables temperature measurement during use. Operating time is logged through the associated disperser T 25 easy clean digital or control. An indication on the display informs the user that maintenance is required.

The easy clean dispersing tool is particularly easy to clean: By turning and lowering the clamp, the shaft and rotor can be dropped down till the whole rotor comes out of the stator. Then the shaft tube of the tool can also be completely rinsed from inside.



designed for scientists

Type of bearing: Ceramic plain bearing  
Product-touching material: AISL 316L, ceramics  
Solvent suitable: Yes  
Sterilizable: Yes, all methods (except for hot air)  
Max. working temperature [°C]: 125  
Shaft length [mm]: 191  
Diameter stator / rotor [mm]: 25 / 18  
Gap between [mm]: 0.5  
Recommended emersion depth [mm]: 45 - 150  
Recommended working range [mL]: 100 - 2000  
Temperature measurement: Yes  
Temperature measurement accuracy:  $\pm 0.5$  K  
Operation time detection: Yes

S 25 EC-T-C-25F is only compatible with the dispersers T 25 easy clean digital and control.



designed for scientists

### Technical Data

Volume range (H <sub>2</sub> O) [l]	0.01 - 2
Stator diameter [mm]	25
Rotor diameter [mm]	18
Gap between rotor and stator [mm]	0.5
allowable Speed max. [rpm]	25000
Circumferential speed max. [m/s]	23.6
Immersion depth [mm]	45 - 150
Shaft length [mm]	191
Material in contact with medium	AISI 316L, ceramic
pH range	2 - 13
Suitable for solvents	yes
Suitable for abrasive substances	yes
Temperature measuring range [°C]	0 - 125
Accuracy of temperature measurement [K]	±1
Working temperature max. [°C]	120
Sterilization methods	all methods except hot air
Ultimate fineness, suspensions [µm]	5 - 25
Ultimate fineness, emulsions [µm]	1 - 5
Weight [kg]	0.634

