

CONTROL UNITS FOR MIXdrive STIRRING DRIVES

Designed for 2mag MIXdrive stirring drives. For chemical, biotechnical and medical applications of all kinds.

MIXcontrol 20

Universal control unit for the connection of 1 stirring drive MIXdrive.

- 20 watts stirring power
- 4-step power setting
- Speed range 100 - 1,600 rpm
- Developed and made in Germany



Type	MIXcontrol 20
Speed range	100 - 1,600 rpm
Stirring power (max.)	20 W
Power setting	4-step (25/50/75/100%)
Material housing	Stainless steel
Permitted operation conditions	0 °C up to +40 °C (at 80% humidity)
Electrical data	100-240 V / 50-60 Hz / 1.5 A
Dimensions (WxDxH)	200 x 155 x 38 mm
Protection category	IP20
Weight (gross)	approx. 1.4 kg
Order no.	90200
Order no. RS232	90210

Individual units and dimensions on request.
3 years warranty on material and manufacturing.
We reserve the right to make technical alterations. We do not assume liability for errors in printing or typing.

Control unit with 20 watts stirring power, speed range from 100 up to 1,600 rpm, jerk-free stirring also at low speeds, power setting (4-steps) for high power with regard to large and viscous stirring amounts and reduced power for the warming-free continuous operation of MIXdrive stirring drives.

Clear digital display for speed- and power settings, SoftStart for reliable catching/centering and safe accelerating of the stirring bar. QuickSet for quick setting of start- and maximum speed, automatic memory function to save the last settings, resistant stainless steel housing, easy to clean.

Also available with RS232 interface.

Interfaces (0-10 volts, 4-20 mA, USB, Ethernet) and customized software adaption on request.

Compatible stirring drives

- MIXdrive 1
- MIXdrive 1 eco (only in combination with distriBOX 4)
- MIXdrive 1 XS (only in combination with distriBOX 4)
- MIXdrive 6
- MIXdrive 15
- MIXdrive 60