



## Technical Datasheet

### 1000 $\mu$ L Filter Barrier Tips

#### PIP1964



#### Specifications

|                           |  |
|---------------------------|--|
| Description               | 1000 $\mu$ L filter barrier tips   |
| Length, mm                | 78   |
| Filters                   | Ultra-High Molecular Weight Polyethylene (UHMWPE) with consistent 20 micron porosity   |
| Colour, Optical Quality   | Natural, virgin, PP, translucent   |
| Low Retention             | Low adhesion, ultra-hydrophobic surface PP   |
| Sterility                 | Gamma irradiation  |
| Graduation                | No   |
| Nominal Capacity, $\mu$ L | 1000   |
| Orifice Style             | Bevelled point   |
| Material Characteristics  | Natural PP, free of heavy metals and softeners<br>Autoclavable at maximum 121°C<br>Suitable for use at -20°C to 90°C                             |
| Product Characteristics   | Physiological harmless/non-toxic<br>Biologically inert<br>RNase, DNase, DNA and pyrogen-free<br>Bevelled point                                   |
| Packaging (Racked)        | 100 tips/rack, 10 racks/pack, 5 packs/case<br>Case specifications: 61 x 51 x 31cm; 0.10cu.m;16.1kg   |
| Storage                   | In dry condition<br>Double boxes and master shipper cases originally closed<br>Storage temperature +4°C to 25°C<br>Pallets should not be stacked |
| Compatibility             | Fits Gilson Pipetman, Eppendorf Research,<br>Sartorius Biohit, Brandtech, CAPP, Finnpipette, HTL,<br>Nichiryo, Sororex                           |