



KEY FEATURES

- 2°C to 10°C temperature range
- External digital controller and temperature display
- Annual service and Calibration Available
- Fitted lock and 2 keys
- Audible and visual temperature alarms
- 2 year warranty as a standard



Flexible Storage

Multiple shelf locations. Back stop on every shelf provides a flexible storage solution.



LED Lighting

Low voltage LED lighting, improves running cost as no heat is produced. Long lasting.

Gross Capacity (litres)	91
Net Capacity (litres)	89
Unit External Width (mm)	479
Unit External Depth (mm)	447
Unit External Height (mm)	845
Product Weight (kg)	20
Packed Width (mm)	515
Packed Depth (mm)	465
Packed Height (mm)	885
Packed Weight (kg)	23
Temperature Range	+2°C to +8°C (set point tolerance + or - 2)
Colour	White
External Finish	Painted Steel
Internal Finish	Painted Plastic
Battery Back up	No
Door Finish	Painted Steel/Solid
Door Type	Solid
Door Style	Hinged, Right hand
Door Liner	Flat
Door Open Depth (mm)	875
Replacement Door Seal	No
Open Door Sensor	No
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 – adjustable
Porthole	Yes
Porthole Location	n/a
Temperature Display on Panel	No
Temperature Alarm	No
Remote Alarm Contacts	No
Audible Alarms	No
Visual Alarms	No
Number of Shelves	2
Number of Shelf Positions	11
Shelf Material	Plastic Coated Wire
Interior Light	Yes
Light Type	LED
Light Activation	Switch
Fan	Yes
Spark Free	No
Controller Type	Manual thermostat
Number of Probes	1
Probe Type	Air only
Ambient Temperature Range	10°C to 30°C
Refrigerant Type	R600a
CFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	No
Voltage Supply	220-240V / 50Hz
Blowing Agent	Cyclopentane
Wall Brackets	Yes
Optional Drawer System	No
Optional Digital Lock	Yes
Other Door Option	n/a
Certification	CE + UKCA
Noise Level (dbA)	39
Input Power (W)	76
Cable Length (CM)	150
Energy Consumption (KW/year)	106
Energy Consumption (KW/24hr)	0.29