

Material description: CONDUCTIVITY STANDARD 1413uS (@25°C) (NIST Traceable)

CAS No: Mixture

Supplied as: Product code Description
CHE4655 CONDUCTIVITY STANDARD 1413uS (@25°C) (NIST Traceable) 1L.

Specification

Parameter	Units	Minimum value	Maximum value	Typical value	Notes
Conductivity @ 5°C	µS/cm			896	
Conductivity @ 10°C	µS/cm			1007	
Conductivity @ 15°C	µS/cm			1139	
Conductivity @ 20°C	µS/cm			1276	
Conductivity @ 25°C	µS/cm	1406	1420	1413	
Conductivity @ 30°C	µS/cm			1550	
Conductivity @ 35°C	µS/cm			1681	
Conductivity @ 40°C	µS/cm			1815	
Conductivity @ 45°C	µS/cm			1949	
Conductivity @ 50°C	µS/cm			2084	
Traceable to NIST					

The reported result was determined by analysis of a sample from this batch taken at time of manufacture. Analysis was performed using an in house method with measurements traceable to NIST SRM 999c. Measurements are derived from and traceable to the SI system of units through the use of balances and thermometers calibrated on a regular basis by UKAS.

Revision date: 20/10/2022

Issue date: 17/09/2024

Specification correct at time of issue but is subject to change without notice. It is the users responsibility to verify the material is suitable for the required application.

Ref: 4655/MS/20221020