

Material description: CONDUCTIVITY STANDARD 12880uS (@25°C)(NIST Traceable)

CAS No: Mixture

Supplied as: Product code Description
CHE4656 CONDUCTIVITY STANDARD 12880uS (@25°C)(NIST Traceable) 1L.

Specification

Parameter	Units	Minimum value	Maximum value	Typical value	Notes
Conductivity @ 5°C	µS/cm			8820	
Conductivity @ 10°C	µS/cm			9330	
Conductivity @ 15°C	µS/cm			10480	
Conductivity @ 20°C	µS/cm			11670	
Conductivity @ 25°C	µS/cm	12816	12944	12880	
Conductivity @ 30°C	µS/cm			14120	
Conductivity @ 35°C	µS/cm			15327	
Conductivity @ 40°C	µS/cm			16550	
Conductivity @ 45°C	µS/cm			17774	
Conductivity @ 50°C	µS/cm			18998	
Traceable to NIST					

The reported result was determined by analysis of a sample from this batch taken at time of manufacture. Analysis was performed using an in house method with measurements traceable to NIST SRM 999c. Measurements are derived from and traceable to the SI system of units through the use of balances and thermometers calibrated on a regular basis by UKAS.

Revision date: 08/11/2023

Issue date: 17/09/2024

Specification correct at time of issue but is subject to change without notice. It is the users responsibility to verify the material is suitable for the required application.

Ref: 4656/MS/20231108