## Characteristics Unitec 3 with glides and footring

ID Bimos: 20023576 ID SLS: SLS5302

Dimensions in mm Seat: H: 580-850

 $\begin{array}{cccc} \text{Packing data} & \text{Weight} & \text{kg} & 14,0 \\ & \text{Volume} & \text{m}^{\text{s}} & 0,15 \end{array}$ 





Base equipment		Benefit
Backrest	Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support.	Healthy posture due to a hump providing support for the back in the lumbar region.
	Backrest height adjustment convenient and easy to handle in sitting position.	The support area can be adapted in accordance to the user's body size.
Seat	Ergonomically designed seat with rounded front edge.	The round front edge of the seat prevents blocked circulation in the thighs.
Seat and backrest design	Synthetic leather upholstery: High-level synthetic leather. Resistant to disinfectants, washable and	The soft and comfortable upholstery provides a comfortable feel.  However, damages caused by sharp parts can not be
	easy-care Selectable in following colours: black (0551) blue (0562)	excluded.  Ideal for the use in production and laboratory.
Seat height	Stepless seat height setting from 580 - 850 mm supported by safety gas spring with protective cover. Using stop-and-go-castors, the seat height increases by 4 cm.	Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt.
Technology	Permanent contact-backrest	This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them.  Thus, the back remains supported all the time. The backrest can also be locked into any tilt position if required.
	Quick adjustment	Every function can be operated comfortable and easy in sitting position.
Base	Black 5 star base made from plastic. Flat design.	Very high stability, longevity and safety Flat design prevents stumbling hazard.
Glides	Wearproof plastic glides with a large surface Area.	Offer a superb level of stability.
Foot ring	Chrome-plated foot ring, adjustable in height.	Provides support through the wide tread area and can be easily and quickly adjusted in height.
Materials	The materials used are recyclable.	Environmentally friendly.

Unitec continue page 2

## characteristics Unitec 3 with glides and footring

Article: 9651 artificial leather

Dimensions in mm

Seat: H: 580-850

Packing data Weight kg 14,0

Volume  $m^3$  0,15

Standards DIN 68 877

German GS "safety tested" mark of confirmity Quality Management System DIN EN ISO 9001

Regulation EWG Nr. 1836/93 and

Environmental

Management System DIN ISO 14001.

Warranty 10 year long term warranty, 3 years full Guaranteed quality and high efficiency.

warranty.



Procuring is insured.



## characteristics Unitec 3 with glides and footring

Article: 9651 artificial leather

Dimensions in mm

Seat: H: 580-850

Packing data 14,0 Weight kg 0,15

Volume т³



Options		Benefit
Armrests	Loop armrest	Made of polyamide, adjustable in width (20 mm).
	Multifunctional armrest	The armrests are adjustable in height, width and depth to suit the individual user.