

'LN65B' - Intelligent LN2 Generators

With ECO & BOOST Technologies

'LN65B' is the latest 'water cooled' Liquid Nitrogen Generator from SLS Products.

Utilising the reliable and efficient PSA technique of separating Nitrogen and Oxygen is used to produce high quality Nitrogen Gas which is then liquefied using our powerful cooling system.

The liquid nitrogen is stored within a suitable sized vacuum insulated tank and the product can be dispensed using a 1.5 metre vacuum insulated hose provided. Other options of dispense methods are available on request.




Features

- Water cooled to ambient temperatures up to +52°C.
- Internal air compressor.
- Nitrogen produced using our own PSA nitrogen generator.
- LN2 at 99% purity.
- Pressure Boost system increasing production
- No Loss Pressure system
- 210 Litre LN2 storage dewar
- All cryogenic parts are vacuum insulated.
- Colour touch screen control.
- Small footprint.
- Low noise.



WATER CHILLER



LN80 DISPLAY

Options

- Internet connectivity
- SMS text messaging
- Closed Loop Water Chiller

The SLS Lab Pro Cryogenics LN65B liquid nitrogen generator is your reliable and efficient on-site plug and produce cryogenic solution. With a small footprint, low power consumption and low cooling water requirement makes the LN65B one of the best solutions available on the market. With cooling water or chiller supplied the system can operate up to +52°C ambient temperatures making it suitable to operate in most parts of the World. Simply connect the power, cooling water and press start for the machine to automatically produce liquid nitrogen when needed. An intelligent level sensor system means you can select the liquid level stop and start using the touch screen controller so you always have enough LN2.

The Pressure 'BOOST' system increases liquid nitrogen production with no additional power or cooling water required, coupled with the 'No Loss' pressure maintaining system making it the most efficient and intelligent GM based technology generator available.

Specifications

Liquid nitrogen production (l/hr)	*2.70
Liquid nitrogen purity	>99% (<1.0% O2)
Liquid nitrogen tank volume (litres)	210
Liquid nitrogen Pressure (bar g)	Up to 4.0*
Power consumption (Kw) – excluding water chiller	6.9
Power supply (1Ø + neutral and earth)	200-240 50/60Hz
LN2 enclosure foot print	1.6m x 0.8m
LN2 enclosure height	1.75m
LN2 enclosure weight	450Kg
Noise level	<65 dBA
Cooling water requirement (kw cooling power)	7.0

LN2 production rate at +25°C and <2,000 metres altitude and at 50Hz (when in boost mode). For higher altitudes please contact your SLS Sales Representative.

*Increased tank pressure and production of LN2 when in boost mode.

Options



Cryogenic safety equipment



O2 depletion alarm



Cryogenic hoses